



# LS864

Medium intensity LED  
obstruction light (Red)

## Compliant to Latest International Standards

- ▶ ICAO Annex 14, Vol 1
- ▶ FAA AC 150/5345-43
- ▶ EASA Aerodromes Design CS-ADR-DSN
- ▶ DGAC / STAC
- ▶ ENAC
- ▶ EASA

## Applications

Medium Intensity Obstruction Lights (MIOL) should be used to warn the presence of obstacles with an height between 45m and 150m

According to Annex 14 of ICAO regulations, Medium Intensity Obstruction Lights (MIOL) should be used to warn the presence of obstacles with an height between 45m and 150m, such as telecommunication towers, wind turbines, chimneys, cranes, buildings and other structures.

Medium Intensity Obstruction Lights include three type of beacons, with different characteristics and uses:

- MIOL, Type A (intensity 20.000cd, day-mode white flashing; 2.000cd, night-mode white flashing) should be used alone;
- MIOL, Type B (intensity 2.000cd, night-mode red flashing) should be used either alone or in combination with Low Intensity Obstacle Lights, Type B or Type E;
- MIOL, Type C (intensity 2.000cd, night-mode red steady burning) should be used either alone or in combination with Medium Intensity Obstacle Lights, Type AC.

the product range also includes DUAL type beacons in the same light fixture, suitable to be used during the day (with white LEDs) and during the night (with red LEDs); these beacons are:

- DUAL MIOL, Type AB (intensity 20.000cd, day-mode white flashing; 2.000cd, night-mode red flashing) should be used in combination with Low Intensity Obstacle Lights, Type B or Type E;
- DUAL MIOL, Type AC (intensity 20.000cd, day-mode white flashing; 2.000cd, night-mode red steady burning) should be used in combination with Medium Intensity Obstacle Lights, Type C.

---

## Features

The LS864-200 Medium Intensity Obstruction Light is compliant to ICAO (Medium Intensity - Type B or C), FAA (Type L-864), ENAC and EASA certified. With a compact body, high quality and ultra-bright LEDs, customized lenses and patented shape for optimum light emission and beacon cooling LS864-200 product is one of the most up-to-date and technologically advanced Aircraft Warning Light.

This LED device is designed to not contain any electronic component (this is available in a separate localised control panel): a huge advantage in terms of increased life-time and suitability to all environments (beacons can stand extreme weather conditions) and in terms of an easy maintenance (in case of maintenance or periodic checks on electronic components, these can be done at ground or easily accessible levels).



# LS864

Medium Intensity LED obstruction light  
solutions (Red)



## Electrical Performance

- Power supply by separate remote control panel (see dedicated datasheet for panel):  
12/24 VDC;  
48 VDC;  
115/230VAC;  
Other power supply range available;
- Average power consumption for MIOL-B (flashing):  
@20fpm: 1,5W  
@40fpm: 3W  
@60fpm: 4,5W
- Average power consumption for MIOL-C (Steady Burning): 21W
- LED feeded at constant current
- No RF-radiations
- Range section of connectable conductors: 0,5mm<sup>2</sup> to 2,5mm<sup>2</sup>
- Cable outer diameter range: 7mm to 14mm

## Mechanical Features

- Anodised aluminium body, painted RAL7035
- Borosilicate glass cover protection
- Silicon rubber, VMQ
- Base wind collector and internal heat sink for optimum cooling
- Degree of protection: IP66
- Anti-condensation Gore-Tex valve
- Lamp unit weight: 6kg
- SS304 beacon support bracket
- Equipped with separate control box for beacon power supply

## Optical Features

- Based on LED technology
- RED light 2.000cd
- Cd emission @ -0,5 and +4
- Horizontal beam radiation: 360
- Vertical beam spread: 4
- PMMA lens
- Light output alignment device

## Environmental Conditions

- |                       |                |                        |                            |
|-----------------------|----------------|------------------------|----------------------------|
| ▶ Ambient Temperature | -30°C to +50°C | ▶ Atmospheric Altitude | up to 10,000 feet ( 3000m) |
| ▶ Storage Temperature | -35°C to +75°C | ▶ Relative Humidity    | 0-100% (sealed unit)       |

Applications	
Air Traffic Control towers (ATC)	Radio and television tower
High buildings	Wind Turbines
Chimney	Tower crane
Pipelines	Radars
Bridges	Antennas
Power transmission pylons	Wind / weather measuring stations

☎ UK: +44 (0) 1942 68 5555 | USA: +1 (239) 985-9406

🌐 [www.atgairports.com](http://www.atgairports.com) ✉ [enquiries@atgairports.com](mailto:enquiries@atgairports.com) ✉ [sales-usa@atgairports.com](mailto:sales-usa@atgairports.com)

LS864

# LS864

Medium Intensity LED obstruction light solutions (Red)



Ordering Codes: LS 864-200

## Application

Medium Intensity Obstruction light

## Beam Type

B = Flashing  
C = Steady

## Unit Type

S = Single  
T = Twin

## Beam options

1 = Omni directional 180°  
2 = Omni directional 360°

## Controller

R = Seperate controller

## Mounting

B = Base  
S = Side

## Version

S = Standard  
I = Infrared

## Other options available

Cloud monitoring system  
TWIN version: two separate LED  
circuits in they same fixture (normal  
+ stand-by)



## Head Office:

atg airports ltd

Lowton Business Park | Newton Road

Lowton St. Mary's | Warrington

WA3 2AP | United Kingdom

THINK  
BEFORE YOU  
PRINT



atg airports reserve the right to change technical data and details at any point in time. Errors may have occurred

UK: +44 (0) 1942 68 5555 | USA: +1 (239) 985-9406

www.atgairports.com enquiries@atgairports.com sales-usa@atgairports.com

Rev 1 - 2021

LS864