



D20 Control Contactor Unit

Features

- Cabling to the unit to be in compliance with Drawing No. (CU M&E) 1675
- Local/Remote Control
- True back indication monitoring actual current flow in the output circuit
- Back indications over a range of currents from 0.25A to 50A
- Please note that it is important that the current which will normally be flowing in the output circuit, is ascertained prior to use. Incorrect tapping of the back indication CT may result in no back indication signal or damage to the back indicator PCB.

Application

The atg D20 units are for the provision of remote control with back indication of mains (415/230V nominal) supplies on Airfields. D20 units will control up to 4 circuits each of which can be monitored to provide back indication of a range of currents from 0.25A to 60A.

Typical circuits are:

- Traffic Light Control
- Road Holding Lights

Options

- Inductive Load Switching
- Wig Wag Control

Standard fittings

- Wall mountable
- IP55 enclosure
- Capable of switching loads up to 60A resistive

Dimensions

Height	520mm
Width	370mm
Depth	240mm
Weight	20kg



atg airports ltd

Lowton Business Park | Newton Road
Lowton St. Mary's | Warrington
WA3 2AP | United Kingdom

atg airports inc

7857 Drew Circle #11
Fort Myers | Florida 33967
USA



📞 UK: +44 (0) 1942 68 5555 | USA: 001 (239) 985-9406

🌐 www.atgairports.com ✉ products@atgairports.com ✉ sales-usa@atgairports.com

D20 Control
Contactor Unit